

10G SFP+ LR 10km

10G Eth, FC, SFP+, LR, 10km, LC, 1310nm, SM

CPP-10E-LR-xDF02

OVERVIEW

The CPP-10E-LR-xDF02 is a single mode SFP+ transceiver designed for 10 Gigabit Ethernet and 10G Fiber Channel applications. It uses a 1310nm DFB laser transmitter and a PIN photodiode receiver and supports transmission distances up to 10km on single mode fiber.

The module supports data rates between 1.0Gbps and 10.7Gbps and is compliant with the SFP+ Multi-Source Agreement and the SFF-8472 Digital Diagnostics Monitoring standard. Real time diagnostics provide monitoring of temperature, supply voltage, transmit power, receive power, and bias current.

The transceiver is available in Commercial (0°C to +70°C) and Industrial (-40°C to +85°C) operating temperature variants which makes it suitable for access networks, data centers, and metro applications.

KEY SPECIFICATIONS

- 10G SFP+ transceiver with duplex LC connector
- 1310nm DFB laser and PIN photodiode receiver
- Supports 1.0Gbps to 10.7Gbps data rates
- Up to 10km transmission distance over single mode fiber
- Less than 1.2 W power consumption
- Temp operating conditions: Commercial (0°C to +70°C) and Industrial (-40°C to +85°C)

TECHNICAL DATA

Parameter	Value	Parameter	Value
Form Factor	SFP+	Transmitter Data:	
Transmission Media	SM (LC)	Tx Power	-6.5 to -0.5dBm ¹⁾
Typical Reach	10km	Tx Wavelength	1270-1350nm
Nominal Wavelength	1310nm	Extinction Ratio	≥ 3.5dB
Data Rate Support	1.0Gbps to 10.7Gbps	Receiver Data:	
Protocol Support	10GbE	Rx Sensitivity	-14.4dBm ¹⁾²⁾
Power Consumption	<1.2W	Rx Overload, max	0.5dBm ²⁾
Operating Temperature	0°C to 70°C / -40°C to 85°C	Rx Wavelength	1260-1600nm
Storage Temperature	-40°C to 85°C	LOS Assert	-30dBm
DDM	Yes	LOS De-assert	-15.5dBm
		LOS Hysteresis	0.5dB

¹⁾ Average Power

²⁾ @ 10.3Gbps. Measured with PRBS 2³¹-1@ BER 1E-12

Safety/Regulatory Compliance

- Class 1 laser safe
- RoHS Compliance

ABSOLUTE MAX RATING

Exceeding these limits can cause permanent damage to the transceiver

Parameter	Value	Parameter	Value
Supply Voltage	-0.5V to 4.5V	Relative Humidity	85%
Storage Temp	-40°C to 85°C	Max Rx Optical Power	0.5dBm

ORDERING INFORMATION

Ordering Code	Description
CPP-10E-LR-CDF02	10G SFP+, LR, 10km, LC, 1310nm, SM, 0 to 70C
CPP-10E-LR-IDF02	10G SFP+, LR, 10km, LC, 1310nm, SM, -40 to 85C

All information contained in this document is subject to change without prior notice at the sole discretion of CloudPhotonix. The company warrants the performance of its products solely in accordance with the current published specifications and applicable warranty terms. CloudPhotonix makes no other warranties, express or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose, or non-infringement of third-party rights. For the most current certification and compliance information, please contact CloudPhotonix directly.

CONTACT INFORMATION

Email: sales@cloudphotonix.com
Phone: +91-1203116709, +91-1203116718
CloudPhotonix India Pvt. Ltd.
Block A-51, Sector 67
Noida – 201301, Uttar Pradesh, India