

1G SFP SX 550m

1G Eth, FC, SFP, SX, 550m, LC, 850nm, MM

CP-GB-SX-xDF02

OVERVIEW

The CP-GB-SX-xDF02 is a multimode transceiver solution designed for short-reach Gigabit Ethernet (GbE) and 1G Fiber Channel (1G FC) applications. It operates over multimode fiber using an 850nm VCSEL laser transmitter and a PIN photodiode receiver, enabling transmission distances up to 550 meters on OM3/OM4 MMF.

The module supports data rates up to 1.25Gbps and complies with the SFP Multi-Source Agreement (MSA) and the DDMI as per SFF-8472 MSA. The diagnostics interface provides real-time monitoring of temperature, voltage, transmit power, receive power, and bias current.

The transceiver is available in Commercial (0°C to +70°C) and Industrial (–40°C to +85°C) temperature ranges, ensuring reliable operation in wide environmental conditions.

KEY SPECIFICATIONS

- 1G SFP transceiver with duplex LC connector
- 850nm VCSEL transmitter and PIN photodiode receiver
- Supports 1.25Gbps Ethernet and 1.063Gbps Fiber Channel applications
- Up to 550m transmission distance over multimode fiber
- Less than 1.0W power consumption
- Temp operating conditions: C-temp (0°C to +70°C) & I-temp (–40°C to +85°C)

TECHNICAL DATA

Parameter	Value	Parameter	Value
Form Factor	SFP	Transmitter Data:	
Transmission Media	MM (LC)	Tx Power	-9 to 0dBm ¹⁾
Typical Reach	550m	Tx Wavelength	830-870nm
Nominal Wavelength	850nm	Extinction Ratio	≥ 9dB
Data Rate Support	100Mbps to 1.25Gbps	Receiver Data:	
Protocol Support	GbE, 1G FC	Rx Sensitivity	-18dBm ^{1) 2)}
Power Consumption	<1.0W	Rx Overload, max	-1dBm ²⁾
Operating Temperature	0°C to 70°C / -40°C to 85°C	Rx Wavelength	830-870nm
Storage Temperature	-40°C to 85°C	LOS Assert	-38dBm
DDM	Yes	LOS De-Assert	-19dBm
		LOS Hysteresis	0.5dB

¹⁾ Average Power

²⁾ @ 1.25Gbps, BER ≤ 1×10⁻¹², PRBS 2⁷-1

Safety/Regulatory Compliance

- Class 1 laser safe
- RoHS Compliance

ABSOLUTE MAX RATING

Exceeding these limits can cause permanent damage to the transceiver

Parameter	Value	Parameter	Value
Supply Voltage	-0.5V to 3.75V	Relative Humidity	85%
Storage Temp	-40°C to 85°C	Max Rx Optical Power	-1dBm

ORDERING INFORMATION

Ordering Code	Description
CP-GB-SX-CDF02	1G SFP, SX, 550m, LC, 850nm, MM, 0 to 70C
CP-GB-SX-IDF02	1G SFP, SX, 550m, LC, 850nm, MM, -40 to 85C

All information contained in this document is subject to change without prior notice at the sole discretion of CloudPhotonix. The company warrants the performance of its products solely in accordance with the current published specifications and applicable warranty terms. CloudPhotonix makes no other warranties, express or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose, or non-infringement of third-party rights. For the most current certification and compliance information, please contact CloudPhotonix.

CONTACT INFORMATION

Email: sales@cloudphotonix.com
Phone: +91-1203116709, +91-1203116718
CloudPhotonix India Pvt. Ltd.
Block A-51, Sector 67
Noida – 201301, Uttar Pradesh, India