

1G SFP BiDi 40km

1G Eth, SFP, BiDi, 40km, LC, 1310/1490nm, SM

CB-GB-40-xxyy02

OVERVIEW

The CB-GB-40-xx4302 and CB-GB-40-xx3402 are single-fiber bidirectional transceiver solutions designed for Gigabit Ethernet (GbE) and 1G Fiber Channel (1G FC) applications. These modules operate over single-mode fiber with complementary wavelength pairs, one variant transmitting at 1490nm and receiving at 1310nm, and the other transmitting at 1310nm and receiving at 1490nm enabling full-duplex communication on a single optical fiber.

Both variants support link distances up to 40km and comply with the SFP Multi-Source Agreement (MSA) and SFF-8472 Digital Diagnostics specification. Digital Diagnostics Monitoring (DDM) provides real-time visibility of parameters such as temperature, supply voltage, transmit power, receive power, and bias current.

Each transceiver integrates a DFB laser and PIN photodiode to deliver stable long-reach optical performance. The modules are available in Commercial (0°C to +70°C) temperature grade to support wide deployment environments.

KEY SPECIFICATIONS

- 1G BiDi SFP transceivers with single LC connector
- Two wavelength options:
 - 1490nm TX / 1310nm RX
 - 1310nm TX / 1490nm RX
- Supports 1.25Gbps Ethernet and 1.063Gbps Fiber Channel applications
- Up to 40km transmission distance over single-mode fiber
- Less than 1.0W power consumption
- Temp operating conditions: C-temp (0°C to +70°C)

TECHNICAL DATA

Parameter	Value	Parameter	Value
Form Factor	SFP BiDi	Transmitter Data:	
Transmission Media	SM (LC)	Tx Power	-5 to 0dBm ³⁾
Typical Reach	40km	Tx Wavelength	1260 –1360nm ¹⁾ 1470 –1510nm ²⁾
Nominal Wavelength	Tx:1310nm Rx:1490nm ¹⁾ Tx:1490nm Rx:1310nm ²⁾	Extinction Ratio	≥9dB
Data Rate Support	10Mbps to 1.25Gbps	Receiver Data:	
Protocol Support	GbE, 1G FC	Rx Sensitivity	-23dBm ^{3) 4)}
Power Consumption	<1.0W	Rx Overload, max	-1dBm ⁴⁾
Operating Temperature	0°C to 70°C	Rx Wavelength	1470 –1510nm ¹⁾ 1260 – 1360nm ²⁾
Storage Temperature	-40°C to 85°C	LOS Assert	-38Bm
DDM	Yes	LOS De-assert	-24dBm
		LOS Hysteresis	0.5dB

¹⁾ CB-GB-40-CD3402 – Blue-coloured latch

²⁾ CB-GB-40-CD4302 – Purple-coloured latch

³⁾ Average Power

⁴⁾ @1250 Mbps, BER ≤1x10⁻¹², PRBS 2⁷-1

Safety/Regulatory Compliance

- Class 1 Laser
- RoHS

ABSOLUTE MAX RATING

Exceeding these limits can cause permanent damage to the transceiver

Parameter	Value	Parameter	Value
Supply Voltage	-0.5V to 3.75V	Relative Humidity	85%
Storage Temp	-40°C to 85°C	Max Rx Optical Power	-1dBm

ORDERING INFORMATION

Ordering Code	Description
CB-GB-40-CD3402	1G SFP, BiDi, 40km, LC, 1310/1490nm, SM, 0 to 70C
CB-GB-40-CD4302	1G SFP, BiDi, 40km, LC, 1490/1310nm, SM, 0 to 70C

All information contained in this document is subject to change without prior notice at the sole discretion of CloudPhotonix. The company warrants the performance of its products solely in accordance with the current published specifications and applicable warranty terms. CloudPhotonix makes no other warranties, express or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose, or non-infringement of third-party rights. For the most current certification and compliance information, please contact CloudPhotonix.

CONTACT INFORMATION

Email: sales@cloudphotonix.com
Phone: +91-1203116709, +91-1203116718
CloudPhotonix India Pvt. Ltd.
Block A-51, Sector 67
Noida – 201301, Uttar Pradesh, India