

10G SFP+ BiDi 20km

10G Eth, SFP+, BiDi, 20km, LC, 1270/1330nm, SM

CB-10E-20-xyyy02

OVERVIEW

The CB-10E-20-CD2302 and CB-10E-20-CD3202 are single-fiber bidirectional SFP+ transceiver solutions designed for 10 Gigabit Ethernet (10GbE) and 10G Fiber Channel applications. They operate over single-mode fiber using complementary wavelength pairs one variant transmitting at 1270nm and receiving at 1330nm, and the other transmitting at 1330nm and receiving at 1270nm enabling full-duplex data transmission on a single optical fiber.

Both modules support data rates up to 10.7Gbps and transmission distances up to 20km. They comply with the SFP+ Multi-Source Agreement (MSA) and the SFF-8472 Digital Diagnostics Monitoring (DDM) standard. DDM provides real-time monitoring of operating parameters such as temperature, voltage, transmit optical power, receive optical power, and laser bias current.

Each module integrates a DFB laser and PIN photodiode to ensure stable long-reach optical performance. The transceivers are available in Commercial (0°C to +70°C) temperature ranges, supporting reliable operation in diverse network environments.

KEY SPECIFICATIONS

- 10G BiDi SFP+ transceivers with single LC connector
- Two wavelength options:
 - 1270nm TX / 1330nm RX
 - 1330nm TX / 1270nm RX
- Supports 10.3Gbps to 10.7Gbps data rates
- Up to 20km transmission distance over single-mode fiber
- Less than 1.2W typical power consumption
- Temp operating conditions: Commercial (0°C to +70°C)

TECHNICAL DATA

Parameter	Value	Parameter	Value
Form Factor	BiDi SFP+	Transmitter Data:	
Transmission Media	SM (LC)	Tx Power	-3 to +2dBm ³⁾
Typical Reach	20km	Tx Wavelength	1260 - 1280nm ¹⁾ 1320 - 1340nm ²⁾
Nominal Wavelength	Tx:1270nm Rx:1330nm ¹⁾ Tx:1330nm Rx:1270nm ²⁾	Extinction Ratio	≥ 3.5dB
Data Rate Support	1Gbps to 10.78Gbps	Receiver Data:	
Protocol Support	10GbE, 10G FC	Rx Sensitivity	-15dBm ^{3) 4)}
Power Consumption	<1.2W	Rx Overload, max	+0.5dBm ⁴⁾
Operating Temperature	0°C to 70°C	Rx Wavelength	1320 - 1340nm ¹⁾ 1260 - 1280nm ²⁾
Storage Temperature	-40°C to 85°C	LOS Assert	-30dBm
DDM	Yes	LOS De-assert	-16dBm
		LOS Hysteresis	0.5dB

¹⁾ CB-10E-20-CD2302 – Black-coloured latch

²⁾ CB-10E-20-CD3202 – Blue-coloured latch

³⁾ Average power

⁴⁾ @10.31Gbps, BER ≤ 1x10⁻¹², PRBS 2³¹-1

Safety/Regulatory Compliance

- Class 1 laser safe
- RoHS Compliance

ABSOLUTE MAX RATING

Exceeding these limits can cause permanent damage to the transceiver

Parameter	Value	Parameter	Value
Supply Voltage	-0.5V to 4.5V	Relative Humidity	85%
Storage Temp	-40°C to 85°C	Max Rx Optical Power	0.5dBm

ORDERING INFORMATION

Ordering Code	Description
CB-10E-20-CD2302	10G SFP+, BiDi, 20km, LC, 1270/1330nm, SM, 0 to 70C
CB-10E-20-CD3202	10G SFP+, BiDi, 20km, LC, 1330/1270nm, SM, 0 to 70C

All information contained in this document is subject to change without prior notice at the sole discretion of CloudPhotonix. The company warrants the performance of its products solely in accordance with the current published specifications and applicable warranty terms. CloudPhotonix makes no other warranties, express or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose, or non-infringement of third-party rights. For the most current certification and compliance information, please contact CloudPhotonix directly.

CONTACT INFORMATION

Email: sales@cloudphotonix.com
Phone: +91-1203116709, +91-1203116718
CloudPhotonix India Pvt. Ltd.
Block A-51, Sector 67
Noida – 201301, Uttar Pradesh, India