

10G SFP+ DAC 1-7m

10G Eth, SFP+, DAC, 1–7m, 24AWG / 30AWG

SD11-10-xxM-yyC1

OVERVIEW

The SD11-10-xxM-yyC1 series is a family of passive Direct Attach Copper (DAC) cables designed for 10 Gigabit Ethernet and 10G Fiber Channel applications. Each assembly integrates SFP+ connectors at both ends and provides a single 10.3Gbps electrical lane for full duplex transmission. The passive copper design offers very low power consumption and simple plug and play operation, making it a cost effective solution for short reach interconnects.

The cable assemblies comply with the SFP+ Multi-Source Agreement and support electrical specifications defined in SFF-8431. They feature controlled impedance, low insertion loss and low crosstalk performance that meets or exceeds industry requirements. Each connector includes an EEPROM that enables module identification and communication with the host system.

The SD11-10 series is available in cable lengths from 1 meter to 5 meters and supports two wire gauge options, 30AWG for shorter lengths and 24AWG for longer lengths. The operating temperature range is 0°C to +70°C which makes these assemblies suitable for top-of-rack switching, server connectivity and high density data center installations.


KEY SPECIFICATIONS

- 10G SFP+ passive DAC cable assemblies
- Supports 10.3Gbps electrical interface
- Low power consumption below 0.1W
- Available lengths: 1m,2m,3m,4m,5m,6m,7m
- Available gauges: 30AWG and 24AWG
- Compliant with SFP+ MSA and SFF-8431
- Controlled impedance with low crosstalk
- Operating temperature: 0°C to +70°C
- Hot pluggable with robust EMI/EMC performance

APPLICATIONS

- 10G Ethernet
- Data centers, Storage Area Networks, Network Attached Storage, Storage servers
- High Bandwidth Switches, Routers

MECHANICAL DRAWING



ORDERING INFORMATION

Ordering Code	Description
SD11-10-01M-30C1	10G SFP+, DAC, 1m, 30AWG, 0 to 70C
SD11-10-02M-30C1	10G SFP+, DAC, 2m, 30AWG, 0 to 70C
SD11-10-03M-30C1	10G SFP+, DAC, 3m, 30AWG, 0 to 70C
SD11-10-04M-24C1	10G SFP+, DAC, 4m, 24AWG, 0 to 70C
SD11-10-05M-24C1	10G SFP+, DAC, 5m, 24AWG, 0 to 70C
SD11-10-06M-24C1	10G SFP+, DAC, 6m, 24AWG, 0 to 70C
SD11-10-07M-24C1	10G SFP+, DAC, 7m, 24AWG, 0 to 70C

All information contained in this document is subject to change without prior notice at the sole discretion of CloudPhotonix. The company warrants the performance of its products solely in accordance with the current published specifications and applicable warranty terms. CloudPhotonix makes no other warranties, express or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose, or non-infringement of third-party rights. For the most current certification and compliance information, please contact CloudPhotonix directly.

CONTACT INFORMATION

Email: sales@cloudphotonix.com
 Phone: +91-1203116709, +91-1203116718
 CloudPhotonix India Pvt. Ltd.
 Block A-51, Sector 67
 Noida – 201301, Uttar Pradesh, India