

25/10G SFP28 BiDi 40km

25/10G Eth, SFP28, BiDi, 40km, LC, 1270/1310nm, SM

CB-25E-40-xDyy02

OVERVIEW

The CB-25E-40-xD1202 and CB-25E-40-xD2102 are single fiber bidirectional SFP28 transceivers designed for 25G Ethernet, eCPRI and CPRI applications. The modules operate using complementary wavelength pairs over a single strand of single mode fiber. One variant transmits at 1270nm and receives at 1310nm, and the other transmits at 1310nm and receives at 1270nm. Both versions support a 25.78/10.31Gbps data rate and provide up to 40km optical reach.

The devices are compliant with the SFP28 Multi-Source Agreement and support Digital Diagnostics Monitoring in accordance with SFF-8472. The DDM interface provides real time monitoring of supply voltage, temperature, transmit optical power, receive optical power and bias current.

The modules operate from a single 3.3V supply and are available in Commercial (0°C to +70°C) and Industrial (-40°C to +85°C) temperature ranges.

KEY SPECIFICATIONS

- 25G BiDi SFP28 transceivers with single LC connector
- Two wavelength options:
 - 1270nm TX / 1310nm RX
 - 1310nm TX / 1270nm RX
- Support for 25/10G Ethernet and CPRI option 10 applications
- Up to 40km distance over SM fiber
- Less than 1.5W power consumption
- Temp operating conditions: Commercial (0°C to +70°C) and Industrial (-40°C to +85°C)

TECHNICAL DATA

Parameter	Value	Parameter	Value
Form Factor	BiDi SFP28	Transmitter Data:	
Transmission Media	SM (LC)	Tx Power	0 to +6dBm ³⁾
Typical Reach	40km	Tx Wavelength	1260-1280nm ¹⁾ 1300-1320nm ²⁾
Nominal Wavelength	Tx:1270nm Rx:1310nm ¹⁾ Tx:1310nm Rx:1270nm ²⁾	Extinction Ratio	≥ 3.5dB
Data Rate Support	25.78/10.31Gbps	Receiver Data:	
Protocol Support	25GbE, CPRI	Rx Sensitivity	-17.5dBm ^{3) 4)}
Power Consumption	<1.5W	Rx Overload, max	-6dBm ⁴⁾
Operating Temperature	0°C to 70°C / -40°C to 85°C	Rx Wavelength	1300-1320nm ¹⁾ 1260-1280nm ²⁾
Storage Temperature	-40°C to 85°C	LOS Assert	-35dBm
DDM	Yes	LOS De-assert	-19dBm
		LOS Hysteresis	0.5dB

¹⁾ CB-25E-40-xD2312 - Red-coloured latch

²⁾ CB-25E-40-xD3122- White-coloured latch

³⁾ Average Power

⁴⁾ @ 25.78Gbps, BER ≤5E-5, PRBS 2³¹-1

Safety/Regulatory Compliance

- Class 1 laser safe
- RoHS Compliance

ABSOLUTE MAX RATING

Exceeding these limits can cause permanent damage to the transceiver

Parameter	Value	Parameter	Value
Supply Voltage	-0.3V to 4V	Relative Humidity	85%
Storage Temp	-40°C to 85°C	Max Rx Optical Power	-6dBm

ORDERING INFORMATION

Ordering Code	Description
CB-25E-40-CD2312	25G/10G SFP28, BiDi, 40km, LC, 1270/1310nm, SM, 0 to 70C
CB-25E-40-ID2312	25G/10G SFP28, BiDi, 40km, LC, 1270/1310nm, SM, -40 to 85C
CB-25E-40-CD3122	25G/10G SFP28, BiDi, 40km, LC, 1310/1270nm, SM, 0 to 70C
CB-25E-40-ID3122	25G/10G SFP28, BiDi, 40km, LC, 1310/1270nm, SM, -40 to 85C

All information contained in this document is subject to change without prior notice at the sole discretion of CloudPhotonix. The company warrants the performance of its products solely in accordance with the current published specifications and applicable warranty terms. CloudPhotonix makes no other warranties, express or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose, or non-infringement of third-party rights. For the most current certification and compliance information, please contact CloudPhotonix directly.

CONTACT INFORMATION

Email: sales@cloudphotonix.com
Phone: +91-1203116709, +91-1203116718
CloudPhotonix India Pvt. Ltd.
Block A-51, Sector 67
Noida – 201301, Uttar Pradesh, India