

1G SFP Copper 100m

1G Eth, SFP, 1000BASE-T, RJ45, 100m

CP-1G-RJ45-xxx2

OVERVIEW

The CP-1G-RJ45-xxx2 is a high-performance Copper SFP transceiver designed for Gigabit Ethernet over Category 5 or better copper cabling. It supports 10/100/1000Mbps operation and provides a maximum reach of 100 meters. The module integrates a full physical layer IC (PHY) that performs 1000BASE-T signalling using 5 level PAM modulation across all four twisted pairs in the cable.

The transceiver complies with the SFP Multi-Source Agreement and IEEE 802.3 standards for 1000BASE-T. It supports both SERDES and SGMII host interfaces and provides access to serial ID information via 2-wire serial interface as defined by the SFF-8472 specification. The fully shielded RJ45 housing ensures excellent EMI performance and stable operation.

The module operates from a single 3.3V supply with typical power consumption around 1.2W. It is available in Commercial (0°C to +70°C) and Industrial (–40°C to +85°C) temperature options. This SFP is suitable for data centers, enterprise switches, routers and copper-based Gigabit Ethernet links up to 100 meters.

KEY SPECIFICATIONS

- 1G SFP transceiver with integrated RJ45 connector
- Supports 10/100/1000Mbps Ethernet
- 100m distance over Cat5 or better UTP cable
- 1000BASE-T PHY using 5 level PAM signaling
- Auto negotiation supported
- Supports both SGMII and SERDES host interfaces
- Low power consumption around 1.2W
- Temp operating conditions: C-temp (0°C to +70°C) & I-temp (–40°C to +85°C)

TECHNICAL DATA

Parameter	Value	Parameter	Value
Form Factor	SFP (Copper)	Interface Standard	1000BASE-T IEEE 802.3
Transmission Media	Electrical (RJ45)	Auto-negotiation	Towards host
Typical Reach	100m	MAC Interface	SERDES or SGMII ¹⁾
Data Rate Support	10Mbps to 1.25Gbps	RxLOS	YES or NO ¹⁾
Protocol Support	GbE		
Power Consumption	<1.2W		
Operating Temperature	0°C to 70°C / -40°C to 85°C		
Storage Temperature	-40°C to 85°C		

¹⁾ Part Number based on MAC Interface & RxLOS pin configs

Safety/Regulatory Compliance

- RoHS

ABSOLUTE MAX RATING

Exceeding these limits can cause permanent damage to the transceiver

Parameter	Value	Parameter	Value
Supply Voltage	3.13V to 3.47V	Relative Humidity	85%
Storage Temp	-40°C to 85°C		

ORDERING INFORMATION

Ordering Code	MAC Interface	Tx_DIS	RxLOS	Description
CP-1G-RJ45-CA02	SERDES	Yes	No	1G, SFP, 100m, RJ45, T Copper, 0 to 70C
CP-1G-RJ45-CB02	SGMII	Yes	Yes	1G, SFP, 100m, RJ45, T Copper, 0 to 70C
CP-1G-RJ45-CB12	SGMII	Yes	Yes	1G, SFP, 100m, RJ45, T Copper, 0 to 70C
CP-1G-RJ45-IA02	SERDES	Yes	No	1G, SFP, 100m, RJ45, T Copper, -40 to 85C
CP-1G-RJ45-IB02	SGMII	Yes	Yes	1G, SFP, 100m, RJ45, T Copper, -40 to 85C
CP-1G-RJ45-IB12	SGMII	Yes	Yes	1G, SFP, 100m, RJ45, T Copper, -40 to 85C

*Other options are also available on request.

All information contained in this document is subject to change without prior notice at the sole discretion of CloudPhotonix. The company warrants the performance of its products solely in accordance with the current published specifications and applicable warranty terms. CloudPhotonix makes no other warranties, express or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose, or non-infringement of third-party rights. For the most current certification and compliance information, please contact CloudPhotonix.

CONTACT INFORMATION

Email: sales@cloudphotonix.com

Phone: +91-1203116709, +91-1203116718

CloudPhotonix India Pvt. Ltd.

Block A-51, Sector 67

Noida – 201301, Uttar Pradesh, India